CP PLUS
enhancing vision

Product Catalogue 2011-2012 (Ver 1.5)

CP PLUS TeknoLogix labs

CCTV Camera | IP Camera | Standalone DVR | PC Based DVR Card | Embedded NVR | Video Door Phones

THE WORLD'S PREFERRED ELECTRONIC SECURITY EQUIPMENT

About Us

W.E. WROLDSEN
Managing Director,
CP Plus GmbH & Co. KG.

Versatile. Robust. State-of-the-art. Every product of CP PLUS, the latest Global offering from CP PLUS GmbH & Co. KG., brings together the passion for quality and security. Where each of its models are launched after rigorous Research & Development by the Tech cell of CP PLUS GmbH & Co. KG., Germany. From retail to public spaces, special events to offices, airports to homes, the CP PLUS product range has solutions for every application.

Manufactured under strict quality control in accordance with International Security Standards, our products are a symbol of Reliability, Performance and Aesthetics. Our cutting-edge, user-friendly technology adds immensely to the credibility of our products and makes us the pioneers in the field of security and surveillance.

Our products range from CCTV Cameras, Digital Video Recorders, and Special Digital Video Recorders to Network Video Recorders like Mobile Digital Video Recorders, Compression Cards and IP cameras. We maintain best-in-class pre-sales and pro-sales services to keep our customers satisfied. We also offer services with customised features and provide professional security and surveillance system solutions to meet various customer demands.

CP PLUS TeknoLogix labs

THE CENTRE OF INNOVATION IN SECURITY TECHNOLOGY

CP PLUS Teknologix labs is the state-of-the-art research & development centre based in Taiwan, which is committed towards innovation and revolutioning video surveillance solutions across security industry worldwide. CP PLUS TeknoLogix Lab provides 'The Perfect Solution', an intelligent and path-breaking technology, being developed by the team of experienced Engineers for different verticals in security industry including retail, education, homes, hotel to name a few.

The CP Plus TeknoLogix Labs is inspired by the power of ideas and innovation, by the need to make things better.

At CP Plus TeknoLogix Labs, the processes that we follow are constantly evolving to keep ahead of technology.

The brains at the CP Plus TeknoLogix Labs have revolutionised the security industry, world-wide.

Analog CCTV Camera

CP PLUS enhancing vision

420 TVL Range of CCTV Cameras

CP-DY42 /-BR
Normal Dome Camera

Features:
- 1/3 " Sony CCD
- 420TVL, 0.2 lux @F1.2
- 3.6mm Fixed Iris Lens
- AGC, AWB, BLC

* CP-DY42-BR (White case)

CP-DY42L2/-Q/-BS/-BQ
Normal IR Dome Camera - 20 Mtr

Features:
- 1/3 " Sony CCD
- 420TVL, 0 lux @F1.2 (IR on)
- 3.6mm fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs

* CP-DY42L2-BS/BQ (White case)

CP-VY42L2-BQ
Normal Vandal Resistant IR Dome Camera- 20 Mtr

Features:
- 1/3" Sony CCD
- 420 TVL, 0 lux @F1.2
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- IP 65 Vandal Resistant Housing

CP-TY42L2/-Q
Normal IR Bullet Camera - 20 Mtr

Features:
- 1/3" Sony CCD
- 420 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- IP 66 Weather Resistant Housing

CP-TY42L2-D
Normal IR Bullet Camera - 20 Mtr

Features:
- 1/3" Sony CCD
- 420 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- IP 66 Weather Resistant Housing

CP-TY42L3/-Q
Normal IR Bullet Camera - 30 Mtr

Features:
- 1/3" Sony CCD
- 420 TVL, 0 lux @F1.2 (IR on)
- 8 mm Fixed Iris Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs
- IP 66 Weather Resistant Housing

CP-TY42L3-D
Normal IR Bullet Camera - 30 Mtr

Features:
- 1/3" Sony CCD
- 420 TVL, 0 lux @F1.2 (IR on)
- 6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs
- IP 66 Weather Resistant Housing

CP-TY42L5/-Q
Normal IR Bullet Camera - 50 Mtr

Features:
- 1/3" Sony Super HAD CCD
- 420 TVL, 0 lux @F1.2 (IR on)
- 12 mm Fixed Iris Lens
- AGC, AWB, BLC
- 84 LEDs, Upto 50 Mtrs
- IP 66 Weather Resistant Housing

480 TVL Range of CCTV Cameras

CP-DY48
Dome Camera

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0.1 lux @F1.2
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC

CP-DY48H1
Dome Camera

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0.1 lux @F1.2
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC

CP-DY48H2
Dome Camera

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0.1 lux @F1.2
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC

CP-DY48MVFA
Vari-Focal Dome Camera with OSD

Features:
- 1/3" Sony Super HAD II CCD
- 480TVL, 0.1lux @F1.2
- 4 ~ 9 mm, Auto Iris Lens
- AGC, AWB, BLC
- OSD

CP-DY48VFH1
Vari-Focal Dome Camera with OSD

Features:
- 1/3" Sony Super HAD II CCD
- 480TVL, 0.1lux @F1.2
- 4 ~ 9 mm, Auto Iris Lens
- AGC, AWB, BLC
- OSD

CP-DY48L2/-BS
IR Dome Camera - 20 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs

* CP-DY48L2 (Black case)

CP-DY48L2H1
IR Dome Camera - 20 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs

CP-VY48L2
Vandal Proof IR Dome Camera - 20 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs, Metal Body

Design and Specifications are subject to change without prior notice.

Analog CCTV Camera

CP PLUS
enhancing vision

CP-VY48L2VFL3
Vandal Proof VF IR Dome Camera - 30 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm vari-focal Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs, Metal Body

CP-BY48
Box Camera

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0.1 lux @F1.2
- C/CS Mount Lens
- AGC, AWB, BLC

CP-TY48L2
IR Bullet Camera - 20 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0 lux @F1.0 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- IP 66 Weather Resistant Housing

CP-TY48L2D
Normal IR Bullet Camera - 20 Mtr

Features:
- 1/3" Sony CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- IP 66 Weather Resistant Housing

CP-TY48L3D
Normal IR Bullet Camera - 30 Mtr

Features:
- 1/3" Sony CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs
- IP 66 Weather Resistant Housing

CP-TY48VFL4
Vari-Focal IR Bullet Camera - 40 Mtr

Features:
- 1/3" Sony Super HAD CCD
- 480 TVL, 0 lux @F1.4 (IR on)
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- 48 LEDs, Upto 40 Mtrs
- IP 66 Weather Resistant Housing

CP-TY48L5
IR Bullet Camera - 50 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 480 TVL, 0 lux @F1.0 (IR on)
- 6 mm Fixed iris Lens
- AGC, AWB, BLC
- 48 LEDs, Upto 50 Mtrs
- IP 66 Weather Resistant Housing

CP-TY48R8
Long Range IR Array Bullet Camera - 100 Mtr

Features:
- 1/3" Sony CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 25 mm Fixed Iris Lens
- AGC, AWB, BLC
- 2 LED Array, Upto 100 Mtrs
- IP 66 Weather Resistant Housing

CP-UA24A4-PR
Array LED weatherproof camera - 40 Mtr

Features:
- 1/3" Sony CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 1pc third-generation array LED, Upto 40Mtrs
- IP 66 Weather Resistant Housing

CP-NA24A4-PR
Array LED Vandalproof Dome Camera - 40 Mtr

Features:
- 1/3" Sony CCD
- 480 TVL, 0 lux @F1.2 (IR on)
- 4 mm Fixed Iris Lens
- AGC, AWB, BLC
- 1pc third-generation array LED, Upto 40Mtrs
- IP 66 Weather Resistant Housing

600 TVL Range of CCTV Cameras

CP-DY60M-E
High Resolution Dome Camera with OSD

Features:
- 1/3" Sony CCD
- 600 TVL, 0.05 lux @F1.2
- 3.6 mm Fixed iris Lens
- AGC, AWB, BLC
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection

CP-DY60MVF-E
High Resolution Vari-Focal Dome Camera with OSD

Features:
- 1/3" Sony CCD
- 600 TVL, 0.05 lux @F1.2
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection

CP-DY60MVB/VY60MVB-E
High Resolution Vari-Focal Dome Camera with OSD

Features:
- 1/3" Sony CCD
- 600 TVL, 0.05 lux @F1.2
- 2.8 ~ 12 mm Auto Iris Lens
- AGC, AWB, BLC, Vandal Proof
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection

* CP-VY60MVB (Vandal Proof)

CP-DY60L2-E
High Resolution IR Dome Camera - 20 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs

Design and Specifications are subject to change without prior notice.

600 TVL Range of CCTV Cameras

CP-DY60VFL3-E

High Resolution Vari-Focal IR Dome Camera - 30 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm, Auto Iris Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs

CP-VY60MVFL3-E

High Resolution Vandal Resistant Vari-Focal Dome Camera - 30 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection
- IP 65 Vandal Resistant Housing

CP-BY60M-E

High Resolution Box Camera with OSD

Features:
- 1/3" Sony CCD
- 600 TVL, 0.05 lux @F1.2
- C/CS Mount Lens
- AGC, AWB, BLC
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection

CP-TY60L2-E

High Resolution IR Bullet Camera - 20 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- IP 66 Weather Resistant Housing

CP-TY60L2D-E

High Resolution IR Bullet Camera - 20 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- IP 66 Weather Resistant Housing

CP-TY60MVFL4-E

High Resolution IR Bullet Camera - 35-40 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm Manual Iris Lens
- AGC, AWB, BLC
- 42 LEDs, Upto 35-40 Mtrs
- IP 66 Weather Resistant Housing

CP-TY60L5-E

High Resolution IR Bullet Camera - 50 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 8 mm Fixed Iris Lens
- AGC, AWB, BLC
- 72 LEDs, Upto 50 Mtrs
- IP 66 Weather Resistant Housing

CP-TY60VFL5-E

High Resolution Vari-Focal IR Bullet Camera - 50 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- 72 LEDs, Upto 50 Mtrs
- IP 66 Weather Resistant Housing

CP-TY60MVFL5-E

High Resolution Mid range Vari-Focal IR Bullet Camera with OSD - 50 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 9 ~ 22 mm Manual Iris Lens
- AGC, AWB, BLC
- 72 LEDs, Upto 50 Mtrs
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter), 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
- IP 66 Weather Resistant Housing

CP-TY60MVFL8-E

High Resolution High Range Vari-Focal IR Bullet Camera with OSD - 80 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 5 ~ 50 mm Manual Iris Lens
- AGC, AWB, BLC
- 12 LEDs, Upto 80 Mtrs (Japanese LED's)
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter), 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
- IP 66 Weather Resistant Housing

CP-TY60MVAR5-E

High Resolution Vari-Focal IR Array Bullet Camera with OSD - 50 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- 3 Units of Dot Matrix Array LED, Upto 50 Mtrs
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter), 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
- IP 66 Weather Resistant Housing

CP-TY60MVER5-E

High Resolution Vari-Focal IR Array Bullet Camera with OSD - 50 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 9 ~ 22 mm Manual Iris Lens
- AGC, AWB, BLC
- 3 Units of Dot Matrix Array LED, Upto 50 Mtrs
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter), 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
- IP 66 Weather Resistant Housing

CP-BY60MW-E

High Resolution Vari-Focal WDR Box Camera

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0.5 lux @F1.2
- C/CS Mount Lens
- AGC, AWB, BLC & WDR
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE

CP-TY60MCVFL12-B

High Resolution Vari-Focal High Range IR Camera withh OSD

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 6 ~ 50 mm Auto Iris Lens
- AGC, AWB, BLC & WDR
- 40+(20+20) LEDs, Upto 120 Mtrs
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter), 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
- IP 66 Weather Resistant Housing

CP-DY60MVFW-E

High Resolution Vari-Focal WDR Dome Camera

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0.01 lux @F1.2 (IR on)
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC & WDR
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE

CP-VY60MVFL3W-E

High Resolution Vari-Focal WDR Dome Camera

Features:
- 1/3" Sony Super HAD II CCD
- 600 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC & WDR
- 36 LEDs, Upto 30 Mtrs
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE

Design and Specifications are subject to change without prior notice.

Effio* Range of 700 TVL CCTV Cameras

CP-DY70M-E

Super High Resolution Dome Camera with OSD

Features:
- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL, 0.01 lux @F1.2
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- OSD, Camera Title, Mirror, Privacy Masking, Motion Detection, D-WDR, 2D-DNR

CP-DY70MVF-E

Super High Resolution Vari-Focal Dome Camera with OSD

Features:
- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL, 0.01 lux @F1.2
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- OSD, Camera Title, Mirror, Privacy Masking, Motion Detection, D-WDR, 2D-DNR

CP-DY70ML2-E

Super High Resolution IR Dome Camera with OSD - 20 Mtr

Features:
- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- OSD, Camera Title, Mirror, Privacy Masking, Motion Detection, D-WDR, 2D-DNR

CP-DY70MVFL3-E

Super High Resolution Vari-Focal IR Dome Camera with OSD 30 Mtr

Features:
- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs
- OSD, Camera Title, Mirror, Privacy Masking, Motion Detection, D-WDR, 2D-DNR

CP-BY70M-E

Super High Resolution Box Camera with OSD

Features:
- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL, 0.01 lux @F1.2
- C/CS Mount Lens
- AGC, AWB, BLC
- OSD, Camera Title, Mirror, Privacy Masking, Motion Detection, D-WDR, 2D-DNR

CP-TY70ML2-E

Super High Resolution IR Bullet Camera with OSD - 20 Mtr

Features:
- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- OSD, Camera Title, Mirror, Privacy Masking, Motion Detection, D-WDR, 2D-DNR
- IP 66 Weather Resistant Housing

CP-TY70ML5-E

Super High Resolution IR Bullet Camera with OSD - 50 Mtr

Features:
- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL, 0 lux @F1.2 (IR on)
- 8mm Fixed iris Lens
- AGC, AWB, BLC
- 72 LEDs, Upto 50 Mtrs
- OSD, Camera Title, Mirror, Privacy Masking, Motion Detection, D-WDR, 2D-DNR
- IP 66 Weather Resistant Housing

CP-TY70MVAR5-E

Super High Resolution Vari-Focal IR Array Bullet Camera with OSD - 50 Mtr

Features:
- 1/3" Sony Super HAD II CCD
- 700 TVL, 0 lux @F1.2 (IR on)
- 4 ~ 9 mm Vari-Focal Lens
- AGC, AWB, BLC
- 3 Units of Dot Matrix Array LED, Upto 50 Mtrs
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter), 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE
- IP 66 Weather Resistant Housing

CP-DY70M

Super High Resolution Dome Camera with OSD

Features:
- 1/3" Sony Ex-View HAD II CCD
- 700 TVL, 0.1 lux @F1.2
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- OSD

CP-DY70MVF

Super High Resolution Vari-Focal Dome Camera with OSD.

Features:
- 1/3" Sony Ex-View HAD II CCD
- 700 TVL, 0.1 lux @F1.2
- 4 ~ 9 mm Auto Iris Lens
- AGC, AWB, BLC
- OSD

CP-DY70ML2

Super High Resolution IR Dome Camera with OSD - 20 Mtr

Features:
- 1/3" Sony Ex-View HAD II CCD
- 700 TVL, 0 lux @F1.2 (IR on)
- 3.6 mm Fixed Iris lens
- AGC, AWB, BLC
- 24 LEDs, Upto 20 Mtrs
- OSD

CP-BY70M

Super High Resolution Box Camera with OSD

Features:
- 1/3" Sony Ex-View HAD II CCD
- 700 TVL, 0.1 lux @F1.2
- C/CS Mount Lens
- AGC, AWB, BLC
- OSD

CP-TY70ML3

Super High Resolution IR Bullet Camera with OSD - 30 Mtr

Features:
- 1/3" Sony Ex-View HAD II CCD
- 700 TVL, 0 lux @F1.0 (IR on)
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC
- 36 LEDs, Upto 30 Mtrs
- OSD
- IP 66 Weather Resistant Housing

CP-TY70MVFL6

Super High Resolution Vari-Focal IR Bullet Camera with OSD - 60 Mtr

Features:
- 1/3" Sony Ex-View HAD II CCD
- 700 TVL, 0 lux @F1.0 (IR on)
- 4 ~ 9 mm Auto Iris lens
- AGC, AWB, BLC
- 78 LEDs, Upto 60 Mtrs
- OSD
- IP 66 Weather Resistant Housing

Design and Specifications are subject to change without prior notice.

Analog CCTV Camera

CP PLUS enhancing vision

Special Range of CCTV Cameras

CP-PY48A-Q
Pin Hole Camera

Features:
- 1/3" Sony CCD
- 480 TVL, 0.8 lux @F1.2
- 3.7 mm Fixed Iris Lens
- AGC, AWB, BLC
- With audio

CP-PY60MA
High Resolution Pin Hole Camera with OSD

Features:
- 1/3" Sony CCD
- 600 TVL, 0.05 lux @F1.2
- 3.7 mm Fixed Iris Lens
- AGC, AWB, BLC
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, 2D-DNR
- With audio

CP-ZY27M
27x Zoom Camera

Features:
- 1/4" Sony CCD
- 480 TVL, 0.5 lux @F1.2
- 3.5 ~ 94.5 mm Motorized Zoom Lens
- AGC, AWB, BLC
- OSD, Camera ID, Camera Title

CP-HY48
Normal Camera - Smoke Detector Housing

Features:
- 1/3" Sony CCD
- 480 TVL, 0.8 lux @F1.2
- 3.6 mm Fixed Iris Lens
- AGC, AWB, BLC

CP-FY60M-E
Metal UFO Dome Camera

Features:
- 1/3" Sony CCD
- 600 TVL, 0.01 lux @F1.2
- 2.8mm Pinhole Lens
- Support Digital- WDR and 2DNR, OSD

CP-SY27CL10-S
27x IR Speed Dome - 100 Mtr IR range with 12 IR Array LED

Features:
- 1/4" Sony CCD
- 480 TVL, 0.3 Lux @ F1.2
- 27X Optical Zoom
- Manual Pan Speed 0.05° ~ 240°/s, Tilt speed 0.03° ~ 160°/s
- 360 Degree continious panning

CP-MY10C
10x Indoor Day & Night Speed Dome Camera

Features:
- 1/4" Sony CCD
- 550 TVL, 0.3 Lux @ F1.2
- 10X Optical Zoom
- Manual Pan Speed 0.05° ~ 240°/s, Tilt speed 0.03° ~ 160°/s
- 360 Degree continious panning

CP-SY22CL12-E
22x IR Speed Dome, 120-150 meters IR range with 72 IR LED

Features:
- 1/4'' Sony Super HAD II CCD
- 540 TVL, 0 Lux When (IR on)
- Manual speed: 0.01 – 120°/s
- Preset accuracy ±0.05° Double cooling fan
- IR LED service life more than 30000 hours
- IP 66 weather proof (High die-cast aluminum housing)

CP-MY22CL10-E
22x IR Night Vision Police VAN Speed Dome Camera

Features:
- 1/4" Sony Ex-View HAD CCD
- Horizontal Resolution of 460 TVL
- Wide Tilt range: +45° ~ -90°
- Long IR coverage of 100 meters
- IP 66 weather proof & Vibration proof design
- Revolutionary integrated and stylish design provides a high wind resistance

CP-SY22CL10-E
22x Laser Light Night Vision Speed Dome Camera

Features:
- 1/4" Sony Ex-View HAD CCD
- Horizontal Resolution of 460 TVL
- Wide Tilt range: +20° ~ -90° , support Auto-flip
- Long IR coverage of 100 meters
- IP 67 weather proof with Wiper and Flap

CP-SY23CL10-EH
23x Outdoor 100 Mtr IR Speed Dome Camera

Features:
- 1/4" Sony Super HAD II CCD
- 540 TVL, 0.1 Lux @ F1.4
- Manual speed: 0.01°/s-180°/s
- 8 Tour and 255 Presets
- 360 Degree continuous panning
- Supports Auto Scan, Auto Cruise and pattern
- IP 67 weather proof housing

CP-SY37CL10-EH
37x Outdoor 100 Mtr IR Speed Dome Camera

Features:
- 1/4" Sony Super HAD II CCD
- 540 TVL, 0.1 Lux @ F1.4
- Manual speed: 0.01°/s-180°/s
- 8 Tour and 255 Presets
- 360 Degree continuous panning
- Supports Auto Scan, Auto Cruise and pattern
- IP 67 weather proof housing

CP-SY23C-EH
23x Outdoor Day & Night Speed Dome Camera

Features:
- 1/4" Sony Super HAD II CCD
- 540 TVL, 0.1 Lux @ F1.4
- Manual speed: 0.01°/s-180°/s
- 8 Tour and 255 Presets
- 360 Degree continuous panning
- Supports Auto Scan, Auto Cruise and pattern
- IP 67 weather proof housing

CP-SY37C-EH
37x Outdoor Day & Night Speed Dome Camera

Features:
- 1/4" Sony Super HAD II CCD
- 540 TVL, 0.1 Lux @ F1.4
- Manual speed: 0.01°/s-180°/s
- 8 Tour and 255 Presets
- 360 Degree continuous panning
- Supports Auto Scan, Auto Cruise and pattern
- IP 67 weather proof housing

CP-SY22C-ET
22x Outdoor Day & Night Speed Dome Camera

Features:
- 1/4" Sony Super HAD CCD
- 480 TVL, 0.1 Lux @ F1.4
- Manual speed: 0.01°/s-180°/s
- 8 Private Zones and 220 Presets
- 360 Degree continuous panning
- Supports Auto Scan, Auto Cruise and pattern
- IP 66 weather proof housing

CP-SY37C-ET
37x Outdoor Day & Night Speed Dome Camera

Features:
- 1/4" Sony Ex-View HAD CCD
- 480 TVL, 0.003 Lux @ F1.4
- Manual speed: 0.01°/s-180°/s
- 8 Private Zones and 220 Presets
- 360 Degree continuous panning
- Supports Auto Scan, Auto Cruise and pattern
- IP 66 weather proof housing

Design and Specifications are subject to change without prior notice.

Key Board Controller

CP-KB31-H

3-axis Control Keyboard

Features:

- Super Control Keyboard
- Electromechanical, RS 485
- Three Dimensional Joystick Control of PTZ Functions
- Display : LED, 7-segment, Pelco- P - D

CP-2020-SP

Super Control Keyboard

Features:

- Super Control Keyboard
- Electromechanical, RS 485
- Variable-speed with zoom
- Display : LED, 7-segment, Pelco- P - D

HD SDI Camera Range

CP-DBY20

HD SDI Box Camera

Features:

- 1/2.8" Sony Progressive Scan CMOS
- 1920 x 1080P@50 fps, 0.2 lux @F1.2
- C/CS Mount Lens
- AGC, AWB, BLC & WDR
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE

CP-TBY20

HD SDI Bullet IR Camera

Features:

- 1/2.8" Sony Progressive Scan CMOS
- 1920 x 1080P@50 fps, 0.2 lux @F1.2
- 3 Pcs. 3rd Generation IR LEDs
- AGC, AWB, BLC & WDR
- OSD, Camera ID, Camera Title, Mirror, Privacy Masking, Motion Detection, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE

Feel secure with world-class technology

Design and Specifications are subject to change without prior notice.

CP-NC9/W-K

HD(720P)@25fps Cube IP camera

Features:
- Progressive Scan CMOS Sensor
- H.264, MJPEG 4 & JPEG Simultaneously
- 720P mode: 30fps, 1280 x 1720
- 4.3 mm Lens, 2 way audio, Internal mic
- 10/100 Ethernet, 802.11n wireless(CP-NC9W-K)
- Includes easy-to-use Viewer & Recorder utility
- 12V DC

CP-ND10/20-R

Full HD Mini Dome IP Camera

Features:
- Progressive Scan CMOS Sensor
- Full HD 1080p @15fps / HD 720p real-time at dual streaming
- H.264 and MJPEG compression
- Power over Ethernet (802.3af)
- Motion Detection
- Privacy Masks
- Security Torx against tampering

CP-ND20VL2-R

Full HD@25fps Vari-Focal IR Dome IP Camera

Features:
- Progressive Scan CMOS Sensor
- Full HD 1080p / HD 720p real-time, dual streaming
- H.264 and MJPEG compression
- Built-in IR Illuminator (effective distance: 30m)
- Motion Detection
- Privacy Masks
- Micro SD support
- Sun Shield & Cable Management

CP-NB20-R

Full HD@25fps Box IP Camera

Features:
- Progressive Scan CMOS Sensor
- Full HD 1080p / HD 720p real-time, dual streaming
- Motion Detection
- Privacy Masks
- Day/Night ICR (optional)
- Auto Iris Lens support
- Micro SD support
- BNC analog output

CP-NT20VL3-R

Full HD@25fps Vari-Focal Bullet IR IP Camera

Features:
- Progressive Scan CMOS sensor
- Full HD 1080p / HD 720p real-time, dual streaming
- H.264 and MJPEG compression
- Built-in IR Illuminator (effective distance: 30m)
- Motion Detection
- Privacy Masks
- Micro SD support
- Sun Shield & Cable Management

CP-NS12/36W-CR

12/36x IP Speed Dome

Features:
- High Resolution 650 TV lines
- H.264 and MJPEG compression
- Preset speed up to 400°/sec
- Alarm In/out
- ICR,WDR
- Auto-Pan/Sequence/Cruise/Calibration
- Digital/Mechanical Image Flip(180°)
- Weatherproof housing (Optional)

CP-NVS6-R

1 Ch. H.264 Video Server

Features:
- 1 Ch. Video Input, 1 video loop out
- H.264 video compression and MJPEG
- 25/30 fps@D1 Resolution
- Dual H.264 Simultaneously H.264 + MJPEG Video Streaming
- 1 alarm inputs /1 alarm outputs
- 20 User Account Supported with password protection
- Power over Ethernet

Embedded NVR

CP-R316Q2-XU

16 Ch. Standalone NVR

Features:
- 16 Ch. @ D1, 8 Ch. @ 720P, 4 Ch. @ 1080P Realtime Recording
- H.264/MPEG4 Dual codec decoding
- Supports 2 Sata HDD, 2 USB
- HDMI & VGA Outputs
- Compatible with Major Brand Cameras

AXIS · Arecont Vision · BOSCH · Honeywell · Panasonic · SANYO · CP PLUS · Canon · DYNACOLOR · SONY · SAMSUNG · ONVIF

CP-R304

4 Ch. Standalone NVR

Features:
- High Quality Live/Playback Video
- Support up to 100fps @ 1.3MP (H.264)
- Compatible with Major Brand Cameras
- E-map and Google Map Event Alert
- Manage up to 4 Network Cameras
- Max. Storage Capacity of 3TB
- Mobile Devices Remote Monitoring

CP-R208

8 Ch. Standalone NVR

Features:
- High Quality Live/Playback Video
- Support up to 200fps @ 1.3MP (H.264)
- Compatible with Major Brand Camera
- E-map and Google Map Event Alert
- Manage up to 8 Network Cameras
- 2 Internal SATA HDD (2TB each)
- Mobile Devices Remote Monitoring

CP-R216

16 Ch. Standalone NVR

Features:
- High Quality Live/Playback Video
- Support up to 400fps @ 1.3MP (H.264)
- Compatible with Major Brand Camera
- E-map and Google Map Event Alert
- Manage up to 16 Network Cameras
- 2 Internal SATA HDD (2TB each) + 1 External SATA (Max. 8TB)
- Mobile Devices Remote Monitoring

Software Based NVR

vOptimus Pro

Features:
- Support H.264 and up to 5 Mega Pixel
- Compatible with Multiple Brand Cameras
- Built-in Intelligent Video Analytics
- Built-in Image Enhancement Tool
- Multi Layer E-Map Monitoring
- 9 Channel Synchronous Playback
- Upto 5 Monitors Auto Detection
- Smart NVR Search
- Multi-monitor Management

vOptimus CMS Basic

Features:
- Manage 16 NVRs or upto 256 Channels
- Support H.264 and up to Full HD
- Built-in Intelligent Video Analytics
- Built-in Image Enhancement Tool
- Dual-layer E-Map Monitoring
- 4 Channel Synchronous Playback
- Smart NVR Search
- Multi-monitor Management

vOptimus Lite

Features:
- Manage 64 IP Cameras
- Support H.264 and up to D1
- Compatible with CP Plus Only
- Upto 3 Monitors Auto Detection
- 4 Channel Synchronous Playback
- Smart NVR Search
- Multi-monitor Management

Design and Specifications are subject to change without prior notice.

Digital Video Recorder

CP PLUS enhancing vision

WD Series

CP-0404H-0808H-1616HD-WD

4/8/16 Ch H.264 Standalone DVR

Features:
- 4/8/16 Ch. Video, 4/8/16 Ch.Audio
- 4CIF(D1)/2CIF/CIF recording resolution
- All Channels simultaneous playback
- 4/8 Ch. - 1 SATA HDD and 16 Ch. - 2 SATA HDD or 1SATA + DVDR/W
- 2 USB Ports, 1 RJ45, RS 485 Port
- TV(BNC)/VGA sync. video output
- Support 3G Mobile phone and email notifications

U Series

CP-0402H-U

4 Channels Entry Level Simple 1U Standalone DVR

Features:
- 4 Ch. Video, 2 Ch. Audio Input
- 4CIF(D1)/2CIF/CIF recording resolution
- All Channels simultaneous playback
- 1 SATA HDD (Max. 2TB)
- 2 USB Ports, 1 RJ45
- TV(BNC)/VGA sync. video output
- Multi-DVR client, DMSS & CMS

CP-0804H-U

8 Channels Entry Level Simple 1U Standalone DVR

Features:
- 8 Ch. Video, 4 Ch. Audio Input
- 4CIF(D1)/2CIF/CIF recording resolution
- All Channels simultaneous playback
- 1 SATA HDD (Max. 2TB)
- 2 USB Ports, 1 RJ45, RS 485 Port
- TV(BNC)/VGA sync. video output
- Multi-DVR client, DMSS & CMS

CP-1604HL-U

16 channel 1U Standalone DVR

Features:
- 16 Ch. Video, 4 Ch. Audio Input
- 4CIF(D1)/2CIF/CIF recording resolution
- All Channels simultaneous playback
- 1 SATA HDD (Max. 2TB)
- 2 USB Ports, 1 RJ45, RS 485 Port
- TV(BNC)/VGA sync. video output
- Multi-DVR client, DMSS & CMS

KRYPTO Series

CP-0401H1/0801H1/1601H1-XU

4/8/16 Ch. H.264, CIF Realtime DVR

Features:
- 4/8/16 Ch. Video, 1 Ch. Audio Input
- D1@6fps/HD1@12fps/CIF@25fps Rec. resolution
- All Channels simultaneous playback
- 1 SATA HDD (Max. 2TB)
- 2 USB, 1 RJ45 & 1 RS485
- TV/BNC/VGA simultaneous video output
- Multi-DVR client, DMSS & CMS

CP-1604H2D-XU

16 Ch. H.264, CIF Realtime DVR

Features:
- 16 Ch. Video, 4 Ch. Audio Input
- D1@6fps/HD1@12fps/CIF@25fps Rec. resolution
- All Channels simultaneous playback
- 2 SATA HDD (Max. 2TB) & CD/DVD-RW
- 2 USB Ports, 1 RJ45, 1 RS232 & RS485 Port
- TV/BNC/VGA/Spot simultaneous Video output
- Multi-DVR client, DMSS & CMS

CP-0404H4D / 0804H4D / 1604H4D-XU

4/8/16 Ch. H.264, CIF Realtime DVR

Features:
- 4/8/16 Ch. Video, 4/4/4 Ch. Audio Input
- D1@6fps/HD1@12fps/CIF@25fps Rec. resolution
- All Channels simultaneous playback
- 4 SATA HDD or 3 SATA +1 CD/DVD-RW
- 2 USB Ports, 1 RJ45, 1 RS232, 1 RS485 & eSATA
- TV/BNC/VGA/Spot/HDMI simultaneous video output
- Multi-DVR client, DMSS & CMS

CP-3216H8D-XU

32 Ch. H.264, CIF Realtime DVR

Features:
- 32 Ch. Video, 16 Ch. Audio Input
- D1@6fps/HD1@12fps/CIF@25fps Rec. resolution
- 16 channel simultaneous playback
- 8 SATA HDD or 6 SATA +1 CD/DVD-RW
- 2 USB Ports, 1 RJ45, 1 RS232, 1 RS485 & eSATA
- TV/BNC/VGA/Spot/HDMI simultaneous video output
- Multi-DVR client, DMSS & CMS

CP-1616M8D-XU

16Ch. 2CIF 2U DVR

2CIF

Features:
- 16ch video & audio
- H.264 & Dual-stream encoding
- Full channel@CIF realtime recording
- HDMI, VGA & BNC output up to 1080P
- 8 SATA, 2 USB

CP-0404Q1/0404/0808/1604Q2-XU

4/4/8/16 Ch. H.264, D1 Realtime DVR

D1

Features:
- 4/4/8/16 Ch. Video, 4/4/8/4 Ch. Audio Input
- D1@25fps Rec. resolution
- All Channels simultaneous playback
- Q1 with 1 SATA and Q2 4/8/16 Ch. 2 SATA HDD (Max. 2TB)
- 2 USB ports, 1 RJ45, 1 RS232 & RS485 port
- TV/BNC/VGA/Spot/HDMI/ simultaneous Video output
- Multi-DVR client, DMSS & CMS

CP-0404Q4D / 0804Q4D / 1604Q4D-XU

4/8/16 Ch. H.264, D1 Realtime DVR

D1

Features:
- 4/8/16 Ch. Video, 4/4/4 Ch. Audio Input
- D1@25fps Rec. resolution
- All Channels simultaneous playback
- 4 SATA HDD or 3 SATA +1 CD/DVD-RW
- 2 USB Ports, 1 RJ45, 1 RS232, 1 RS485 & eSATA
- TV/BNC/VGA/Spot/HDMI simultaneous Video output
- Multi-DVR client, DMSS & CMS

CP-0404Q8D / 0808Q8D / 1616Q8D-XU

4/8/16 Ch. H.264, D1 Realtime DVR

D1

Features:
- 4/8/16 Ch. Video, 4/8/16 Ch. Audio Input
- D1@25fps Rec. resolution
- All Channels simultaneous playback
- 8 SATA HDD or 6 SATA +1 CD/DVD-RW
- 2 USB Ports, 1 RJ45, 1 RS232, 1 RS485 & eSATA
- TV/BNC/VGA/Spot/HDMI simultaneous video output
- Multi-DVR client, DMSS & CMS

RADO Series

CP-0404H/0804H-XT

4/8 Ch. H.264, CIF Realtime DVR

Features:
- 4/8 Ch. Video, 4/4 Ch. Audio Input
- CIF@25Fps Recording
- 1 SATA HDD (Max. 2TB)
- 2 USB Ports, 1 RJ45, 1 RS232, 1 RS485
- BNC/VGA simultaneous video output
- Multi-DVR client & CMS

CP-0404HD/0804HD/1604HD-XT

4/8/16 Ch. H.264, CIF Realtime DVR

Features:
- 4/8/16 Ch. Video, 4/4/4 Ch. Audio Input
- D1 recording selection is available on each channel
- All Channels simultaneous playback
- 2 SATA HDD (Max. 2TB), DVDRW option
- 2 USB Ports, 1 RJ45, 1 RS232, 1 RS485
- BNC/VGA/HDMI simultaneous video output
- Multi-DVR client & CMS

PLUTO Series

CP-0404/0808/1616H2-NL

4/8/16 Ch. H.264,CIF Realtime DVR

Features:
- 4/8/16 Ch. Video, 4/8/16 Ch. Audio Input
- 100/200/400Fps H.264 CIF Recording
- 2 SATA HDD (Max. 2TB)
- 2 USB Ports, 1 RJ45, 1 RS485
- BNC/VGA simultaneous video output
- Multi-DVR client & CMS

CP-2408/3204H4-NL

24/32 Ch. H.264,CIF Realtime DVR

Features:
- 24/32 Ch. Video, 8/8 Ch. Audio Input
- 600/800Fps H.264 CIF Recording
- 4 SATA HDD (Max. 2TB)
- 2 USB Ports, 1 RJ45, 1 RS485
- BNC, VGA & HDMI video output
- Multi-DVR client & CMS

Design and Specifications are subject to change without prior notice.

Digital Video Recorder

CP PLUS enhancing vision

HD-SDI Series

CP-0404HD8-XU

4 Ch. H.264, HD-SDI Realtime DVR

Features:
- 4 Ch. HD-SDI Video, 4 Ch Audio Input
- 4 Ch. loop out
- 100/120Fps@1080P Recording
- 8 SATA HDD or 6 SATA (Max. 2TB)+1 CD/DVD-RW
- 3 USB Ports, 1 RJ45, 1 RS232, 1 RS485 & eSATA
- TV/BNC/VGA/HDMI simultaneous video output
- Multi-DVR client, DMSS & CMS

ATM DVR

CP-0402HL5-U

4 Channel ATM Standalone DVR

Features:
- 4 Ch. Video, 2 Ch. Audio Input
- 4CIF(D1)/2CIF/CIF recording resolution
- All Channels simultaneous playback
- 4 SATA HDD (Max. 2TB Each)
- 2 USB Ports, 1 RJ45, RS 232, RS 485 Port
- TV(BNC)/VGA/HDMI, In-Built 5.6" LCD
- ATM/POS, Multi-DVR client, DMSS & CMS

COMBO DVR

CP-0404-0804HL10-U

4/8 Ch Combo DVR

Features:
- 4/8 Ch. Video, 4/8 Ch.Audio Input
- 4CIF(D1)/2CIF/CIF recording resolution
- All Channels simultaneous playback
- 1 SATA 2.5" HDD
- 2 USB Ports, 1 Ethernet, RS 485 Port
- TV(BNC)/Built-in 10" LCD Monitor
- Multi-DVR client, DMSS & CMS

MOBILE DVR Series

CP-0404MH1S-TS

4 Ch. H.264, CIF Realtime Mobile DVR

Features:
- 4 Ch. Video, 4 Ch Audio Input
- 4CH CIF at 30FPS/25FPS
- SD card recording max.32GB
- GPS Option : Vehicle positioning, Speed detection, Synch time
- 1 USB Port & 1 RS232
- 6 Sensor Inputs & 1 Output
- Watermark : prevents the video to be tempered

CP-0404MH1V-TS

4 Ch. H.264, CIF Realtime Mobile DVR

Features:
- 4 Ch. Video, 4 Ch Audio Input
- 4CH CIF at 30FPS/25FPS
- 1 SATA 2.5" HDD
- GPS Option : Vehicle positioning, Speed detection, Synch time
- 1 USB Port
- 6 Sensor Inputs & 1 Output
- Watermark : prevents the video to be tempered

CP-0404MH2V-TS

4 Ch. H.264, CIF Realtime Mobile DVR

Features:
- 4 Ch. Video, 4 Ch Audio Input
- 4CH CIF at 30FPS/25FPS
- 2.5" SATA HDD
- GPS, Wifi, G sensor, 3G Options
- 1 USB Port
- 8 Sensor Inputs & 1 Output
- Watermark : prevents the video to be tempered

DVR Cards

CP-9404/9808A-L

Features:
- 8 Ch real-time, 16 Ch non real-time
- 10 Bits high video quality
- Super Network function, Dynamic IP supported.
- Remote view picture or view through mobile-phone
- Better compatibility with PC components: support popular motherboards (Intel, AMD) integrated graphic cards and PCI-E
- One system support 32chs; user can playback 32chs Simultaneously

CP-9404/9804

Features:
- 4/8 channel real time monitoring
- One PC Can Support Two Cards
- Multi screen monitoring, 1,4,9,16 split Screen
- All Channel playback
- Support local and remote PTZ control.
- Supports Remote Viewing over IE and through client software

Design and Specifications are subject to change without prior notice.

Video Door Phone

CP-VK40-VP

4" TFT Color Video Door Phone

Features:
- Hands Free
- Camera: waterproof, anti-vandal with name plate
- Max 4 monitors, Max 2 outdoor units with power supply

CP-VK70-VP

7" TFT Color Video Door Phone

Features:
- Hands Free
- Camera: waterproof, anti-vandal with name plate
- Max 4 monitors, Max 2 outdoor units

CP-VK70T-VP

7" TFT Color Video Door Phone

Features:
- Feather Touch
- Hands Free
- Camera: waterproof, anti-vandal with name plate
- Max 4 monitors, Max 2 outdoor units

CP-VK70M-VP

7" TFT Color Video Door Phone with memory

Features:
- Hands Free
- Camera: waterproof, anti-vandal with name plate
- Max 4 monitors, Max 2 outdoor units with power supply

CP-VM40-VP

4" TFT Color Monitor

Features:
- Hands Free
- Camera: waterproof, anti-vandal with name plate
- Max 4 monitors, Max 2 outdoor units with power supply

CP-VM70-VP

7" TFT Color Monitor

Features:
- An indoor extension unit
- Compatible with VP Series only (Max 4 indoor units)
- Hands free, with power supply

CP-VC5BC-VP

Features:
- An outdoor extension unit
- Compatible with VP Series only (Max 2 indoor units)
- Waterproof, anti-vandal, name plate

CP-VM40B-VP

Features:
- An indoor extension unit
- Compatible with VP Series only (Max 4 indoor units)
- 4" CRT Black & White, A class Tube, with power supply (No cable is supplied with this unit)

CP-VCP21-PB

Features:
- Main outdoor station
- Big LCD
- In Built Colour Camera with IR
- Appearance color: Black / Silver
- Anti-vandal, Waterproof, Flush-mounted, Aluminum alloy panel

CP-VCP21W-PB

Features:
- Common outdoor station
- Big LCD
- In Built Colour Camera with IR
- Appearance color: Black / Silver
- Anti-vandal, Waterproof, Flush mounted, Aluminum alloy panel

CP-VCP21-PB

Features:
- Main outdoor station with Access Card
- Big LCD
- Access control function
- In Built Colour Camera with IR
- Color Vision
- Appearance color: Black / Silver
- Anti-vandal, Waterproof, Flush mounted, Aluminum alloy panel

CP-VCP22-PB

Features:
- Main outdoor station, Direct pressing key
- Big LCD
- In Built Colour Camera with IR
- Appearance color: Black / Silver
- Anti-vandal, Waterproof, Flush mounted, Aluminum alloy panel

CP-VNCP21-PB

Features:
- Main outdoor station - TCP/IP
- High Resolution CCD
- Big keypad for inputting room number password unlocking
- Big LCD for display
- Stainless steel panel and flush mounted
- Speaker and microphone, waterproof IP66
- LED penetrative light, access control and Voice leading for option
- Leaving visitor's message for option, with power supply

CP-VNM70-PB

Features:
- Indoor Monitor unit - TCP/IP
- 7 inch Touch Screen
- Talk, Call, Monitor and unlock
- Alarming, calling guard station
- 6 alarm areas for sensors and detectors
- Setting/canceling code alarm,
- Image and message recording and reading
- Calling talking between any apartments
- Various mode for in-home, out-home, and sleeping etc. with power supply

CP-VM70-PB

Features:
- 7 Inch Indoor Monitor Unit
- Door Releasing / Monitoring/listening / Hand-free talking
- Surface Mounted
- Set room Number
- Emergency call for help and call guard station
- Appearance color: white, Color vision
- Image memory for option

CP-VM40-PB

Features:
- 4 Inch Indoor Monitor Unit
- Surface Mounted,
- Set room Number
- Emergency call for help and call guard station
- Door Releasing / Monitoring/listening / Hand-free talking,
- Appearance color: White, Color vision
- Image memory for option

Design and Specifications are subject to change without prior notice.

Video Door Phone

CP PLUS
enhancing vision

CP-VG67-PB

Features:
- Gaurd Station
- Master Network System
- Big LCD for display
- Display: Digital LCD display
- Display: Alarm records , message memory
- Display: Display address from outdoor station & monitor, calling extension unit
- Talking: Talk with outdoor station, wall outdoor station, as well as door releasing

CP-VSCP4-PB

Features:
- Short Circuit Protector
- Power Source: DC15V
- Can Support 4 Monitors
- Size:170x97x50mm

CP-VNC6-PB

Features:
- Network Connector
- Power Source: DC15V
- Can Support 1 building
- Size:170x97x50mm

CP-VPSM12-PB

Features:
- Power Supply
- Input: AC110V/60HZ-AC240V/50HZ
- Output: DC15V/2A
- Can support 12 indoor phones working

CP-VPSG2-PB

Features:
- Power Supply of guard station
- Input: AC110V/60HZ-AC240V/50HZ
- Output: Two groups of DC15V/2A
- Can support one guard station working

CP-VPSCP2-PB

Features:
- Power Supply of wall outdoor station
- Input: AC110V/60HZ-AC240V/50HZ
- Output: Two groups of DC15V/2A
- Can support power supply to outdoor station

CP-VIM200-PB

Features:
- Image memory
- Power Source: DC15V
- Can Support 1 building
- Size:170x97x50mm
- Can save 1000 PC pictures

CP-VC35C-PB

Features:
- An outdoor camera to be used outside the flats
- Nano-glass shield, aluminum alloy, waterproof, antivandal, name plate

Because great homes deserve

State-of-the-art security

Protect your most precious possessions with
CP Plus Video Door Phones

THE WORLD'S PREFERRED ELECTRONIC SECURITY EQUIPMENT

CE FC RoHS Compliant

Design and Specifications are subject to change without prior notice.

*EFFIO, SUPER HAD, EXVIEW are Registered trademarks of Sony Corporation

CP PLUS
enhancing vision

WORLD WIDE PRESENCE

THE WORLD'S PREFERRED ELECTRONIC SECURITY EQUIPMENT

CP PLUS
enhancing vision

CP PLUS GMBH & CO. KG.
Hans Henny Jahnn Weg 9, D22085 Hamburg, Germany, Tel: +49-40-22705-114
Email : sales@cpplusworld.com, Website : www.cpplusworld.com